

SX



SX shown with Pearl shell



SX shown with Pearl shell,  
Coastal Gray cabinet and Polymer step

<b>Seating Capacity</b>	3 adults
<b>Dimensions</b>	6' x 6' x 33"/1.83m x 1.83m x .84m
<b>Water Capacity</b>	285 gallons/1,075 liters
<b>Weight</b>	720 lbs./325 kg dry; 3,620 lbs./1,640 kg filled*
<b>Spa Shell Options</b>	Pearl or Desert
<b>Cabinet Options</b>	Coastal Gray, Espresso or Teak
<b>Jets - 17</b>	1 Moto-Massage® jet 16 Directional Precision® jets
<b>Waterfall</b>	n/a
<b>Jet Pump 1</b>	Wavemaster® 6200; Two-speed 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque
<b>Jet Pump 2</b>	n/a
<b>Circulation Pump (Optional)</b>	SilentFlo 5000®
<b>Water Care System</b>	FROG® In-Line Cartridge Ready
<b>Ozone System (Optional)</b>	FreshWater® III Corona Discharge
<b>Control System</b>	IQ 2020® 115v/20 amp** (Includes G.F.C.I. protected power cord) or 115v/30amp*** or 220v/50amp***, 60Hz
<b>Lighting</b>	Blue LED light, dimmable; Splendors® multi-colored LED light, dimmable (optional)
<b>Heater</b>	No-Fault® 1000w/115v
<b>Energy Efficiency</b>	FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law
<b>Effective Filtration Area</b>	30 sq. ft., top loading
<b>Vinyl Cover</b>	3" to 2" tapered, 1 lb. density foam core Ash, Caramel or Chestnut
<b>Cover Lifter (Optional)</b>	CoverCradle®, CoverCradle II, Lift 'n Glide®
<b>Steps (Optional)</b>	Everwood® or Polymer Coastal Gray, Espresso or Teak

\* Includes water and 3 adults weighing 175 lbs. each.

\*\* Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.

\*\*\* G.F.C.I. protected sub-panel required in 30amp conversion or 220v mode.  
Export models available in 230v, 50Hz, 1000w heater.

From the makers of

