



RECSPORT[™] Recreation Systems by Endless Pools®

OWNER'S MANUAL

WELCOME



Watkins Wellness congratulates you on your decision to enjoy the finest Recsport™ Recreation System available. Welcome to the growing family of RECSPORT Recreation System by ENDLESS POOLS owners.

OWNER'S MANUAL

This Owner's Manual will acquaint you with the operation and general maintenance of your new **RECSPORT** Recreation System. We suggest that you take some time to carefully review all sections. Please keep this manual available for reference.

If you have questions about any aspect of your **RECSPORT** Recreation System's set-up, operation or maintenance, contact your authorized **ENDLESS POOLS** dealership. They are trained professionals who are familiar with the product, as well as new **RECSPORT** Recreation System ownership concerns. Their expertise will facilitate the enjoyment of your new **RECSPORT** Recreation System.

The serial number/identification label is located within the equipment compartment of your **RECSPORT** Recreation System. The serial number should also be documented on the delivery receipt from your dealer.

For product registration of your RecSport Recreation System, please visit the following site: https://endlessfitness.com/fitness-system-owner/

IMPORTANT: Watkins Wellness reserves the right to change specifications, or design, without notification and without incurring any obligation.

DATE PURCHASED:
DATE INSTALLED:
DEALER:
ADDRESS:
TELEPHONE:
MODEL/SERIAL NUMBER:
COVER SERIAL NUMBER:

In most cities and counties, permits will be required for the installation of electrical circuits or the construction of exterior surfaces (decks and gazebos). In addition, some communities have adopted residential barrier codes which may require fencing and/or self-closing gates on the property to prevent unsupervised access to the **RECSPORT** Recreation System by children. As a general practice, your local Building Department will inform you of any applicable barrier requirements at the time a permit is obtained for the installation of an electrical circuit. Your **ENDLESS POOLS** dealer can provide information on which permits may be required.

TABLE OF CONTENTS

SAFETY INFURMATION	WATER QUALITY AND MAINTENANCE
IMPORTANT SAFETY INSTRUCTIONS1	BASIC INFORMATION1
IMPORTANT RECSPORT RECREATION SYSTEM	CHEMICAL SAFETY1
INSTRUCTIONS	HOW TO ADD CHEMICALS TO THE WATER1
SITE REQUIREMENTS	FUNDAMENTALS OF WATER MAINTENANCE1
INDOOR CONSIDERATIONS4	THE ENDLESS POOLS WATER MAINTENANCE
OUTDOOR CONSIDERATIONS4	PROGRAM
ELECTRICAL REQUIREMENTS	VACATION WATER CARE INSTRUCTIONS1
230 VOLT PERMANENTLY CONNECTED5	GLOSSARY1
EQUIPMENT COMPARTMENT6	CARE AND MAINTENANCE
DOOR PANEL REMOVE & REPLACE6	FILTER MAINTENANCE1
GETTING STARTED	FILTER CARTRIDGE REMOVAL AND CLEANING INSTRUCTIONS1
RECSPORT RECREATION SYSTEM FEATURES7	DRAINING YOUR RECSPORT RECREATION
HYDROMASSAGE JETS8	SYSTEM2
SWIM JETS 8	WINTERIZING YOUR RECSPORT RECREATION SYSTEM2
WATERFALL VALVE8	CARE OF THE PILLOWS2
AIR CONTROLS8	CARE OF THE EXTERIOR2
QUICK START-UP INSTRUCTIONS8	
OPERATING INSTRUCTIONS	SERVICE INFORMATION
CONTROL PANEL10	GENERAL INFORMATION2
SETTINGS10	GFCI AND HIGH LIMIT THERMOSTAT2
SMART WINTER MODE11	MISCELLANEOUS SERVICE INFORMATION2
AUDIO IN.STREAM 2™ (OPTIONAL)12	ACTS INVALIDATING WARRANTY2
TEMPERATURE CONTROL12	DISCLAIMERS2
JETS CONTROL	WATKINS WELLNESS CUSTOMER SERVICE2
LIGHT CONTROL 13	TROUBLESHOOTING2
FILTER CYCLES	
POLLING13	
ALL OFF / MEMORY ON13	
WI-FI IN.TOUCH™ 2 (OPTIONAL)13	

SAFETY INFORMATION

IMPORTANT SAFETY INSTRUCTIONS

(READ AND FOLLOW ALL INSTRUCTIONS)

AVOIDING THE RISK TO CHILDREN

M DANGER - RISK OF CHILD DROWNING

Extreme caution must be exercised to prevent unauthorized access by children. To avoid accidents, ensure that children cannot use a **RECSPORT** Recreation System unless they are supervised at all times.

⚠ WARNING

To reduce the risk of injury, do not permit children to use this **RECSPORT** Recreation System unless they are closely supervised at all times.

- To reduce the risk of injury, lower water temperatures are recommended for young children. Children are especially sensitive to hot water.
- Extreme caution must be exercised to prevent unauthorized access by children. To avoid accidents, ensure that children cannot use the RECSPORT Recreation System unless they are supervised at all times.

DO:

- Make sure you always lock any child resistant locks after using the RECSPORT Recreation System for your children's safety.
- Test the water temperature with your hand before allowing children to enter the RECSPORT Recreation System to be sure that it's comfortable.
- Remind children that wet surfaces can be very slippery. Make sure that children are careful when entering or exiting the RECSPORT Recreation System.

DON'T:

- Allow children to climb onto a RECSPORT Recreation System cover.
- Allow children to have unsupervised access to the RECSPORT Recreation System.

AVOIDING THE RISK OF ELECTROCUTION

DANGER - RISK OF ELECTROCUTION

- · Connect only to a grounded source.
- Do not bury the power cord. A buried power cord may result in death, or serious personal injury due to electrocution if direct burial-type cable is not used, or if improper digging occurs.
- A ground terminal (pressure wire connector) is provided on the control box inside the unit to permit connection of a minimum No. 8 AWG solid copper bonding conductor between this point and any metal equipment, metal water pipe, metal enclosures of electrical equipment, or conduit within five feet (1.5 m) of the unit as needed to comply with

NO DIVING

Danger: Diving may result in serious injury or death.



local requirements.

- Do not connect any auxiliary components (for example, cable, additional speakers, headphones, additional audio components) to the audio system unless approved by Watkins Wellness
- Do not self service the audio component by opening or removing RECSPORT Recreation System door panel as this may expose dangerous voltage or other risk of injury. Refer all servicing to qualified service personnel.
- Do not attach an external antennae to a RECSPORT Recreation System audio system unless installed by a licensed electrician in accordance with Article 810 of the National Electric Code, ANSI/NFPA 70.

MARNING

- To reduce the risk of electrical shock, replace a damaged cord immediately. Failure to do so may result in death or serious personal injury due to electrocution.
- Your RECSPORT Recreation System is provided with a Ground Fault Circuit Interrupter (GFCI) for user and equipment protection. To ensure proper operation of this important safety device, test according to the following instructions:
 - A ground terminal is provided inside the junction box. To reduce the risk of electric shock, connect this terminal to the grounding terminal of your electrical service or supply panel with a continuous green, insulated copper wire. The wire must be equivalent in size to the circuit conductors supplying the equipment. In addition, a bonding terminal (pressure wire connector) is provided on the outside of the control box/heater for bonding to local ground points. To reduce the risk of electric shock, this connector should be bonded with a No. 6 AWG solid copper wire to any metal ladders, water pipes, or other metal within 5 feet (1.5 m) of the RECSPORT Recreation System to comply with local requirements. The means of disconnection must be readily accessible, but must be installed at least 5 feet (1.5 m) from the RECSPORT Recreation System.
 - Your RECSPORT Recreation System is provided with a suitably rated circuit breaker to open all ungrounded supply conductors.
 - Your RECSPORT Recreation System uses ground fault circuit interrupters in the electrical subpanel. Before each use of the RECSPORT Recreation System and with the unit operating, push the TEST button on each breaker. The switch should click over to the "Trip" position. Wait 30 seconds and reset each GFCI breaker by switching it completely off and then completely on. The switch should then stay on. If either of the interrupters does not perform in this manner, it is an indication of an electrical malfunction and the possibility of an electric shock. Disconnect the power until the fault has been identified and corrected.

A DANGER - RISK OF ELECTRICAL SHOCK

 Install at least 5 feet (1.5 m) from all metal surfaces. A RECSPORT Recreation System may be installed within 5 feet (1.5 m) of a metal surface if each metal surface is permanently connected by a

- minimum No. 8 AWG solid copper conductor attached to the wire ground connector on the heater terminal block that is provided for this purpose.
- Install your RECSPORT Recreation System in such a way that drainage is away from the electrical compartment and from all electrical components.
- Do not permit any electrical appliances, such as a light, telephone. radio, or television within 5 feet (1.5 m) of a **RECSPORT** Recreation System. Failure to maintain a safe distance may result in death, or serious personal injury due to electrocution, if the appliance should fall into the **RECSPORT** Recreation System.

DO:

- · Be sure your RECSPORT Recreation System is connected to the power supply correctly - use a licensed electrical contractor.
- Disconnect the RECSPORT Recreation System from the power supply before draining the RECSPORT Recreation System or servicing the electrical components.
- Test the Ground Fault Circuit Interrupter(s) before each use.
- Replace audio components only with identical components (if your RECSPORT Recreation System is equipped with an audio component).

DON'T:

- Use the RECSPORT Recreation System with the equipment compartment door removed.
- Place electrical appliances within 5 feet (1.5m) of the RECSPORT Recreation System.
- Use an extension cord to connect the RECSPORT Recreation System to its power source. The cord may not be properly grounded and the connection is a shock hazard. An extension cord may cause a voltage drop, which will cause overheating of the jet pump motor and motor damage.
- · Attempt to open the electrical control box. There are no user serviceable parts inside.

RISKS TO AVOID

DANGER - RISK OF INJURY

- To reduce the risk of injury to persons, DO NOT remove suction fittings (filter standpipes) located in the filter compartment.
- The suction fittings in the RECSPORT Recreation System are sized to match the specific water flow created by the pump. Never replace a suction fitting with one rated less than the flow rate marked on the original suction fitting.
- · There is a danger of slipping and falling. Remember that wet surfaces can be very slippery. Take care when entering or exiting the **RECSPORT** Recreation System.
- Never operate RECSPORT Recreation System if the suction fittings are broken or missing.
- People with infectious diseases should not use the RECSPORT Recreation System.
- Keep any loose articles of clothing, long hair, or hanging jewelry away from rotating jets or other moving components. Long hair should be tied up or placed under a bathing cap.
- Safe water temperature for aquatic Recreation is approximately 85°F (29.5°C).
- DO NOT use this RECSPORT Recreation System alone.

INCREASED SIDE EFFECTS OF MEDICATION

- The use of drugs or alcohol may cause unconsciousness with the possibility of drowning.
- Persons using medications should consult a physician before using a **RECSPORT** Recreation System; some medication may cause a user to become drowsy, while other medication may affect heart rate, blood pressure, and circulation.
- Persons taking medications which induce drowsiness, such as tranquilizers, antihistamines, or anticoagulants should not use the **RECSPORT** Recreation System.

HEALTH PROBLEMS AFFECTED BY RECSPORT RECREATION SYSTEM USE

- Pregnant women should consult a physician before using **RECSPORT** Recreation System.
- Persons suffering from obesity, or with a medical history of heart disease, low or high blood pressure, circulatory system problems, or diabetes should consult a physician before using RECSPORT Recreation System.

UNCLEAN WATER

Keep the water clean and sanitized with correct chemical care. The recommended levels for your ENDLESS POOLS RECSPORT Recreation System are:

Free Available Chlorine:	Total Alkalinity:
1 - 5 ppm	80 - 120 ppm
Water pH:	Calcium Hardness:
7.2 - 7.8	75 - 150 ppm

 Refer to Water Quality and Maintenance section for complete instructions.

IMPORTANT: Turn on the jet pump for a least ten minutes after adding ANY RECSPORT Recreation System water chemicals into the filter compartment.

Clean the filter cartridges monthly to remove debris and mineral buildup which may affect the performance of the hydromassage jets, limit the flow, or trip the high limit thermostat, which will turn off the entire **RECSPORT** Recreation System.

AVOIDING THE RISK OF HYPERTHERMIA

Prolonged immersion in hot water can result in HYPERTHERMIA, a dangerous condition which occurs when the internal temperature of the body reaches a level above normal 98.6°F (37°C). The symptoms of hyperthermia include unawareness of impending hazard, failure to perceive heat, failure to recognize the need to exit the **RECSPORT** Recreation System, physical inability to exit the **RECSPORT** Recreation System, fetal damage in pregnant women, and unconsciousness resulting in a danger of drowning.

⚠ WARNING

The use of alcohol, drugs, or medication can greatly increase the risk of fatal hyperthermia in **RECSPORT** Recreation Systems.

TO REDUCE THE RISK OF INJURY

- The water in the RECSPORT Recreation System should never exceed 99°F (37.5°C). Water temperatures between 79°F and 99°F (26°C and 37.5°C) are considered safe for a healthy adult. The lower water temperatures are recommended for extended use (exceeding ten minutes) and for young children. Extended use can cause hyperthermia.
- Pregnant or possibly pregnant women should limit RECSPORT
 Recreation System water temperatures to 85°F (29.5°C) consult a
 physician prior to using this product. Failure to do so may result in
 permanent injury to your baby.
- Do not use RECSPORT Recreation System having water temperatures over 100°F (36°C) immediately following strenuous Recreation.
- Keep all breakables, especially glass, away from this RECSPORT Recreation System.
- Never insert any objects into any openings.
- Keep all chemicals away from children and pets.
- · DO NOT stack chemicals on top of one another.
- NEVER MIX CHEMICALS.
- Sanitizing chemicals must be stored separately from balancing chemicals.

AVOIDING THE RISK OF SKIN BURNS

- To reduce the risk of injury, before entering a RECSPORT Recreation System the user should measure the water temperature with an accurate thermometer.
- Test the water with your hand before entering the RECSPORT Recreation System to be sure it's comfortable.

SAFETY SIGN

Each ENDLESS POOLS RECSPORT Recreation System is shipped with a SAFETY SIGN in the owner's package. The sign, which is required as a condition of Product Listing, should be permanently installed where it is visible to the users of the RECSPORT Recreation System. To obtain additional SAFETY SIGNS, contact your ENDLESS POOLS dealer. Safety labels that are affixed to the shell are intended to be permanent and should not be removed.

IMPORTANT RECSPORT RECREATION SYSTEM INSTRUCTIONS

The following contains important **RECSPORT** Recreation System information, and we strongly encourage you to read and apply them.

DO:

- Follow the RECSPORT Recreation System Care and Maintenance recommendations stated in this manual.
- Use only approved accessories and recommended RECSPORT Recreation System chemicals and cleaners.

DON'T:

- Leave the RECSPORT Recreation System exposed to the sun without water or a cover in place. Exposure to direct sunlight can cause solar distress of the shell material.
- Roll or slide the RECSPORT Recreation System on its side. This will damage the siding.
- Lift or drag the vinyl cover by using the cover lock straps; always lift or carry the cover by using the handles.
- Attempt to open the electrical control box. There are no user serviceable parts inside. Opening of the control box by the RECSPORT Recreation System owner will void the warranty. If you have an operational problem, carefully go through the steps outlined in the Troubleshooting section. If you are not able to resolve the problem, contact your authorized ENDLESS POOLS dealer. Many problems can easily be diagnosed over the telephone by an Authorized Service Technician.

RECSPORT RECREATION SYSTEM SHELL

Your **RECSPORT** Recreation System has an acrylic shell. Stains and dirt generally will not adhere to your **RECSPORT** Recreation System's surface. A soft rag should easily remove most dirt. Most household chemicals are harmful to your **RECSPORT** Recreation System's shell (see below for detailed information on cleaning agents). Always rinse off any **RECSPORT** Recreation System shell cleaning agent with fresh water.

IMPORTANT:

- 1. The following products are the ONLY approved cleaning agents for your RECSPORT Recreation System shell: plain water, or Soft Scrub[®]. The use of alcohol or any other household cleaner other than those listed to clean the RECSPORT Recreation System shell surface is NOT recommended. DO NOT use any cleaning products containing abrasives or solvents since they may damage the shell surface, specifically: Simple Green[®], Windex[®] or spa Mitt. NEVER USE HARSH CHEMICALS! Damage to the shell by use of harsh chemicals is not covered under the warranty. Always rinse off any RECSPORT Recreation System shell cleaning agent with fresh water.
- Iron and copper in the water can stain the RECSPORT Recreation System shell if allowed to go unchecked. Ask your ENDLESS POOLS dealer about a Stain and Scale Inhibitor to use if your RECSPORT Recreation System has a high concentration of dissolved minerals.
- 3. Keep all cleaners out of the reach of children and use care when applying.

SAVE THESE INSTRUCTIONS

SITE REQUIREMENTS

Your **RECSPORT** Recreation System must be installed on a smooth and level surface that can support the dead weight listed in the back of this manual.

If a new slab is poured, consult your local electrical codes regarding grounding and bonding. Local code may require a bonding wire to be attached to the reinforcing bar or wire mesh that is embedded in the concrete. If new concrete is being poured, this is the ideal time to install the conduit for the incoming electrical supply.

Even if a new pad has been poured, it is essential that the system site is level and planar. There is a simple way to ensure that this is the case. First, draw a chalk outline of the footprint of your **RECSPORT** Recreation System. Place a six-foot level along and around the footprint of the system. Verify that there are no gaps between the level and floor. Next pour water inside of the chalk footprint. Verify that the water does not puddle inside the footprint.

Should there a be a gap or should the water puddle inside the footprint, call your **ENDLESS POOLS** dealer prior to continuing to discuss the best way to resolve this situation.

INDOOR CONSIDERATIONS

- Local electrical and plumbing codes.
- Ventilation fans and/or dehumidifiers should be provided to handle the humidity developed by your RECSPORT Recreation System. Walls, ceiling and wood trim should be water resistant, also.
- Chemicals will vaporize from the water and may cause an odor and possibly corrosion to certain home hardware. Never store chemicals inside the RECSPORT Recreation System cabinet.
- 4. During the normal use of the RECSPORT Recreation System, water will escape the vessel. Never place on or over any materials, which may be damaged by this water or the chemicals within the water. Keep damageable materials far enough away to avoid water damage, even if the RECSPORT Recreation System should lose all its water.
- Consider and prepare for the unlikely event of rapid drainage. If
 placement of the RECSPORT Recreation System is permanent,
 you may wish to provide floor drains to accommodate draining, etc.
 Always leave room all around the RECSPORT Recreation System
 for easy access in case repairs are necessary.
- 6. Consider and prepare for the unlikely event of removal.
- 7. Do not set **RECSPORT** Recreation System on finished floor without a waterproof barrier protection underneath.
- The RECSPORT Recreation System should have access to a
 power source capable of supplying 230 volts AC power. It must
 be wired directly into a grounded circuit with a ground fault circuit
 interrupter (GFCI). No other appliances should be on the same
 circuit.
- The RECSPORT Recreation System should be close to a source of water.
- Do not use the RECSPORT Recreation System above a finished living area due to the risk of water damage.
- The RECSPORT Recreation System is not designed for in-floor installation. However, it is compatible with a deck system that is built flush with the bar top, provided you leave access for service.
- Be sure to note any other considerations, such as aesthetics or privacy concerns that may affect the safety or enjoyment of using the RECSPORT Recreation System.

OUTDOOR CONSIDERATIONS

- 1. Local electrical and plumbing codes.
- Consider local codes pertaining to fencing, enclosures, walls, electrical and plumbing. You will need to ensure that your RECSPORT Recreation System is an adequate distance from power lines, both above ground and underground. Your RECSPORT Recreation System will also need to be child proofed.
- 3. View from house for aesthetics and supervisory needs.
- 4. Distance from house for wintertime soaking.
- 5. Nighttime lighting.
- Consider sunlight exposure, views, access, property lines, lighting, wind direction, shielding, septic tanks, plants, and trees when determining your location. Chemicals in the RECSPORT Recreation System water may splash damaging nearby plant life.
- If your RECSPORT Recreation System is to be located on a second story, be positive support is adequate. Call your builder and a structural engineer.
- Area for placement of support equipment where adequate space will be needed to gain access to components for maintenance and general servicing.
- Be sure to note any other considerations, such as aesthetics or privacy concerns that may affect the safety or enjoyment of using the RECSPORT Recreation System.
- Provide adequate drainage away from the equipment and adequate elevation to allow draining by siphon, if should be required.
- Location of electrical supply. 230-volt systems require hard wire installed from the main electrical source, to the sub panel, then to the RECSPORT Recreation System terminal block. All equipment must be ground fault circuit protected. All electrical wiring must comply with the national electric code.
- 12. Locations at least 5 ft (1.5 m) from all metal surfaces. A RECSPORT Recreation System may be installed within 5 feet (1.5 m) of metals surfaces providing each metal surface is permanently connected by a no. 8 awg copper conductor attached to the bonding wire connector on the heater provided for this purpose. All installations must comply with article 680 of the U.S. national electric code and ANSI/NFPA 70-1984.

ELECTRICAL REQUIREMENTS

IMPORTANT: Fill the **RECSPORT** Recreation System with water before turning on the power.

Your **ENDLESS POOLS RECSPORT** Recreation System has been carefully designed to give you maximum safety against electrical shock. Connecting the **RECSPORT** Recreation System to an improperly wired circuit will negate many of the **RECSPORT** Recreation System's safety features. Improper wiring may also cause electrocution, risk of fire, and other risks of injuries. Please read and follow the electrical installation requirements and instructions completely!

230 VOLT PERMANENTLY CONNECTED

ENDLESS POOLS RECSPORT Recreation Systems must be wired in accordance with all applicable local electrical codes. All electrical work should be done by an experienced, licensed electrician. We recommend the use of appropriate electrical conduit, fittings, and wire for all circuits.

The diagram below illustrates how to wire the RECSPORT Recreation System model:

- An electrical subpanel containing a 30 Amp breaker is included with your RECSPORT Recreation System. We recommend that this subpanel be used to supply power to the RECSPORT Recreation System.
- The subpanel requires a 30 amp, single phase, 230 volt, four wire service (two line, one neutral, one ground). The grounding conductor must not be less than #8 AWG. Refer to local codes and to NEC 250-122 (table).

- Mount the subpanel in the vicinity of the RECSPORT Recreation System, but not closer than five feet away, in accordance with all local codes. (N.E.C. 680-38 to 41-A-3)
- Open RECSPORT Recreation System by removing the 4 screws holding the vertical T-spacer located in the center of the equipment compartment (back side of RECSPORT Recreation System). Slide panel towards center and remove, repeat for other panel.
- Insert power wires into RECSPORT Recreation System from either side towards the bottom, you will find a plastic cap attached to wall.
- Once your RECSPORT Recreation System has been filled with water, turn it on and test all of the circuit breakers.

IMPORTANT: If breaker immediately trips, verify that the wires are correctly connected. Breaker should be tested prior to each use. Here's how:


- Push the "TEST" button on each GFCI breaker, and observe it click OFF.
- Wait 30 seconds, then push the breaker switch to the OFF (down) position (to ensure that it has completely disengaged), then push the breaker switch to the ON (up) position. If you don't wait 30 seconds, the RECSPORT Recreation System's power indicator may continue to blink try again.

If the GFCI breakers fails to operate in this manner, your **RECSPORT** Recreation System may have an electrical malfunction, and you may be at risk of electrical shock. Turn off all circuits and do not use the **RECSPORT** Recreation System until the problem has been corrected by an authorized service agent.

WARNING: Removing, or bypassing any GFCI breaker will result in an unsafe RECSPORT Recreation System and will void the RECSPORT Recreation System's warranty.


IMPORTANT: If you ever need to move or relocate your **ENDLESS POOLS RECSPORT** Recreation System, it is essential that you understand and apply these installation requirements. Your **ENDLESS POOLS RECSPORT** Recreation System has been carefully engineered to provide maximum safety against electric shock. Remember, connecting the **RECSPORT** Recreation System to an improperly wired circuit will negate many of its safety features.

NOTE: Long wiring runs may require larger-gauge wire than stated.



EQUIPMENT COMPARTMENT

The illustration below is to be used as a reference only (your **RECSPORT** Recreation System may look different). The equipment compartment is located behind the hydromassage seats (back of the **RECSPORT** Recreation System).



- Hydromassage Jets & Filter Pump
- 2. Swim Jets Pump
- 3. Control Box & Heater
- 4. Bonding Terminal
- 5. Ozone Unit

- 6. Bluetooth Music (optional)
- 7. Subwoofer (optional)
- 8. Wi-Fi (optional)
- Isolation Valve

CAUTIONS

USE COPPER CONDUCTORS ONLY.

USE SUPPLY WIRES SUITABLE FOR 167°F/75°C.

DISCONNECT ALL SUPPLY CONNECTIONS BEFORE SERVICING.
CONNECT ONLY TO A CIRCUIT PROTECTED BY A CLASS A
GROUND-FAULT INTERRUPTER.

THESE RECSPORT RECREATION SYSTEMS ARE INTENDED FOR USE WITH GFCI SUBPANEL PROVIDED.

INCORRECT WIRING WILL DAMAGE CIRCUIT BOARDS.

REFER TO THE WIRING INSTRUCTIONS INCLUDED WITH THE SUB-PANEL FOR DETAILED WIRING INSTRUCTIONS.

DOOR PANEL REMOVE & REPLACE

REMOVAL

- 1. Locate the vertical T-spacer in the center of the equipment compartment (back side of RECSPORT Recreation System).
- 2. Remove the 4 screws (using a Philips screw driver) holding the T-spacer then remove the T-spacer.
- 3. Slide panel towards center until panel is no longer behind corner.
- 4. While holding panel, first pull panel up then pull bottom away from **RECSPORT** Recreation System.
- 5. Lower panel to remove. Repeat for other side.

REPLACE

- 1. Raise panel making sure it goes behind the bar top then lower to rest on bottom frame
- 2. Slide panel behind corner.
- 3. Replace other side panel using steps 1 & 2.
- 4. Attach T-spacer back in place using 4 screws to complete the installation.



GETTING STARTED

MAIN RECSPORT RECREATION SYSTEM FEATURES

(Your Recreation System may look different)



1) The **control panel** provides a quick visual check of the **RECSPORT** Recreation System's status and allows the user to set different functions of the **RECSPORT** Recreation System.



2) The **Air Valve** allows you to add air to your hydromassage jets.



3) The **Water Feature Valve** adjusts the amount of water that flows from the water feature.



4) The **Swim** jets provide a strong flow of water creating a current to swim against.



5) The **Large Hydromassage jets** provide a unique, pulsating massage.



6) The **Midsize Directional Hydromassage** jets, with eyeball nozzles, deliver a direct, more focused massage.



7) The **Midsize rotational Hydormassage** jets, provide a rotating massage.



8) The **Mini Hydromassage** jets feature a direct more focused massage.



9) Pillow



10) Swim Speaker (Optional)



11) Seating area Speaker (Optional)



12) Suction Screen




ADDITIONAL RECSPORT RECREATION SYSTEM FEATURES

- 13) Water feature
- 14) Ozone Jet/Heater Return
- 15) Grab Rails
- 16) Filter Compartment Grill
- 17) Points of light
- 18) Row Bar Anchor
- 19) Tether Anchor


HYDROMASSAGE JETS

LARGE HYDROMASSAGE JETS - This jet provides a unique, pulsating massage. The water flow is adjustable in that it can be turned from low to high (by rotating the jet faceplate ¼ turn).






MIDSIZE DIRECTIONAL JET - These jets allow you to redirect the jet stream by changing the position of the nozzle. The water flow is adjustable in that it can be turned from low to high (by rotating the jet faceplate ½ turn).



MIDSIZE ROTATIONAL JET - These jets provide a rotating massage pattern. The water flow is adjustable in that it can be turned from low to high (by rotating the jet faceplate ½ turn).




MINI JET - These jets deliver a direct, more focused massage. The water flow is adjustable in that it can be turned from low to high (by rotating the jet faceplate 1/4 turn).



SWIM JETS

SWIM JET - The Swim Jet provides a powerful stream of water used to simulate a water current.



WATERFALL VALVE

Your **RECSPORT** Recreation System is equipped with a waterfall feature. It is activated by turning on the hydromassage jets (either low or high speed). The flow is regulated by turning the waterfall valve on the inside wall of the **RECSPORT** Recreation System.



AIR CONTROLS

Your **RECSPORT** Recreation System is equipped with two air valves. The air valves will add or remove air to the hydromassage jet system. Rotate valve to see which hydromassage jets are affected.



QUICK START-UP INSTRUCTIONS

BEFORE YOU FILL YOUR **RECSPORT** RECREATION SYSTEM

Make sure your **RECSPORT** Recreation System has been properly installed per all local codes, this includes the location of the **RECSPORT** Recreation System, the foundation of the **RECSPORT** Recreation System, as well as the electrical installation of the **RECSPORT** Recreation System. Installation instructions in the form of a Pre-Delivery Instruction booklet can be obtained online.

DO:

- Know which water treatment system you will be using and make sure you have necessary chemicals available. Read all of the instructions that come with the system.
- Have 5-way Test Strips Available.
- · Have pH/Alkalinity Up & Down available.
- Know the hardness of your water, contact your dealer to help you with this information. See Water Quality and Maintenance for more information.
- Purchase the Clean Screen® pre-filter to remove unwanted contaminants from the tap water. This is recommended, not required.

DON'T:

- Fill the RECSPORT Recreation System with hot water or cold water with cold water temperature below 50° F (10° C)! Tripping of the highlimit thermostat may result causing your RECSPORT Recreation System to stop functioning.
- Fill the RECSPORT Recreation System with "softened" water that is outside WATKINS WELLNESS recommended range, as this may damage the RECSPORT Recreation System's equipment. See Water Quality and Maintenance for more information.

START-UP

Your ENDLESS POOLS RECSPORT Recreation System has been thoroughly tested during the manufacturing process to ensure reliability and long-term customer satisfaction. A small amount of water may have remained in the plumbing after testing and, as a result, may have spotted the RECSPORT Recreation System shell or the RECSPORT Recreation System siding prior to delivery. Before filling the RECSPORT Recreation System, wipe the RECSPORT Recreation System shell clean with a soft rag. The following instructions must be read and followed exactly to ensure a successful start-up or refill.

CAUTIONS

- Do NOT fill the RECSPORT Recreation System with hot water, as tripping of the high-limit thermostat may result.
- DO NOT CONNECT POWER TO AN EMPTY RECSPORT
 Recreation System. Power to the RECSPORT Recreation System
 automatically activates critical components within the RECSPORT
 Recreation System, such as controls, heater, and other systems.
 If power is supplied to these components prior to the RECSPORT
 Recreation System being filled, the components will be damaged, and
 this may result in a non-warranty component failure.
- DO NOT use your RECSPORT Recreation System after filling until all
 of the steps listed below are completed.
- DO NOT add chlorine if treating your RECSPORT Recreation System with polyhexamethylene biguanide (Biguanide, PHMB, eg. BaquaSpa[®]) sanitizer.
- Before filling your RECSPORT Recreation System for the first time, remove the equipment compartment door and check to ensure that the unions on either side of the pump(s) and heater are hand-tight and the slide valves are open.
 - 1. CLOSE DRAIN, remove the filter compartment grill skimmer tray and one filter (pg. 19). Fill your RECSPORT Recreation System through the filter compartment using the CleanScreen™ pre-filter that attaches to your garden hose. The water level of your RECSPORT Recreation System should be maintained at a level 6" (15 cm) below the top of the RECSPORT Recreation System. Reinstall the filter, skimmer tray, and grill once the RECSPORT Recreation System is filled.

IMPORTANT: Watkins Wellness does not recommend that the **RECSPORT** Recreation System be filled with "softened" water, as this may damage the **RECSPORT** Recreation System's equipment.

- AFTER THE RECSPORT RECREATION SYSTEM HAS BEEN FILLED with water and the equipment compartment door is secured, power must be applied to the RECSPORT Recreation System.
 - · FIRST activate power to the subpanel from the main house panel.
 - NEXT open the door of the electrical subpanel and reset the GFCI breaker.
 - · FINALLY, close and secure the subpanel door.
- 3. TO CHECK THE OPERATION OF THE JET SYSTEM and to purge any remaining air from the heating system complete the following steps:
 - Press the jets button and place all jet pumps on High.
 - Once the jet system is fully operational (as indicated by strong, non-surging jets), priming of the RECSPORT Recreation System is complete.

- To turn off the jets, press all of the jets button on the control panel to turn off the jets.
- If you do not feel a steady stream of water from your jets, refer to the instructions for priming the pump in the RECSPORT Recreation System TROUBLESHOOTING section.
- 4. SET THE TEMPERATURE CONTROL to the desired temperature between 59°F (15°C) and 99°F (37.5°C). The RECSPORT Recreation System temperature is pre-programmed to reach 85°F (29.5°C). You may change the water temperature by pressing the ▲ button on the control panel to raise the temperature, or lower temperature by pressing the ▼ button. Place the RECSPORT Recreation System cover on the RECSPORT Recreation System and allow the water temperature to stabilize approximately 1°F (0.5°C) per hour. Make sure you secure the cover in place. Periodically check the RECSPORT Recreation System water temperature. When the water temperature reaches desired temperature, proceed to the next step.
- 5. USING A TEST STRIP AND APPLICABLE CHEMICALS adjust Total Alkalinity (TA) to 80 - 120 ppm, Calcium Hardness (CH) to 75 - 150 ppm, then RECSPORT Recreation System water pH to between 7.2 and 7.8. These procedures are listed in the "Water Quality and Maintenance" section.
 - **OPERATION NOTE:** Adjusting the Total Alkalinity as the first step is important, as out-of balance TA will affect your ability to adjust the pH correctly and will prevent the sanitizer from operating effectively.
 - **IMPORTANT:** Activate all the jets (press the jets buttons and place all jet pumps on high for 10 minutes) before adding chemicals. Disperse the chemicals in the swim area away from the walls.
- 6. SUPERCHLORINATE the RECSPORT Recreation System WATER by adding 1½ teaspoons of chlorine (sodium dichlor) per 250 gallons (950 liters) of water while running the jets on high for 10 minutes. Disperse the chemicals in the swim area away from the walls.
- 7. TEST THE RECSPORT Recreation System WATER FOR CHLORINE RESIDUAL. If the residual is between 1 and 5 ppm on the test strips, go on to the next step. If the residual is less than 1 ppm, activate the jets on high speed for another 10 minutes and add more chlorine as needed, then retest.
- WARNING: High sanitizer levels can cause discomfort to the user's eyes, lungs and skin. Always allow the sanitizer level to fall to the recommended range before using the RECSPORT Recreation System
- 8. **RECHECK** the Total Alkalinity (TA) 80 120 ppm, Calcium Hardness (CH) 75 150 ppm, and the pH must be between 7.2 and 7.8.

The RECSPORT Recreation System is ready for use when the RECSPORT Recreation Syste m water has circulated and the bromine level remains between 1 and 2 ppm or chlorine level remains between 1 and 5 ppm.

OPERATION NOTE: For proper water circulation during the tenminute cycle place the air control lever in OFF position.

OPERATING INSTRUCTIONS

CONTROL PANEL


The control panel provides a bright, full color display, and intuitive user experience, while its screen's high resolution brings **RECSPORT** Recreation System user interfaces to a new level. Loaded with a large amount of memory and a powerful on-board processor creating seamless graphic interface that **RECSPORT** Recreation System users have been waiting for.



CONTROL PANEL FUNCTIONS

When the screen is off, press any button to turn the control panel screen on and display the home screen. After 30 minutes of inactivity the screen will shut off

The function description of the buttons below will only work from the Home screen. Once the control panel is placed in a submenu the selection lights next to the buttons will light up to indicate which buttons may be selected for a specific screen function.



SETTINGS

One press of the (2) (Settings button) from the home page gives you access to a menu to manage the settings of your **RECSPORT** Recreation System where you will find:

- Water care
- Audio (optional)
- Maintenance
- · Date and time
- Keypad Settings
- Miscellaneous
- · Wi-Fi (optional)
- Electrical configuration
- Factory reset
- About

Use the \bigcirc or \bigcirc buttons to move up and down in the list. To select an option, press the lit button beside the desired highlighted option.

IMPORTANT: At any point you can press the (2) (Settings button) to return to the home screen or top left button (hydromassage jets) to go back.

WATER CARE

The Water Care section will help you set up your ideal filtration and heating settings. Choose from Away from Home, Beginner, Energy Savings, Super Energy Savings, and Weekender, depending on your needs.



Use (middle left) button to choose your setting. A green check mark will appear on the selected icon to confirm.

When in Economy mode, the heating set point will be reduced by 20°F (11°C), which means that the heating system will not come on during the set time unless the temperature falls 20°F (11°C) below the set temperature.

The filtration schedule shown on the screen will apply to the main filtration pump (hydromassage jets).

WATER CARE MODES

mu K

Away from home:

In this mode the System will always be in economy mode; the set point will be reduced by 20°F (11°C).



Beginner:

The System will never be in economy mode and will be filtering according to the pack's low level configuration.



Energy Savings:

The System will be in economy mode during the peak hours of the day and resume normal mode on the weekend*.



Super Energy:

The System will always be in economy mode during peak hours, every day of the week*.



Weekender:

The System will be in economy mode from Monday to Friday, and will run normally on the weekend*.



Default Settings:

By selecting this setting you will be asked to confirm your choice. Doing so will revert all Water Care Modes back to factory settings.

*Filtration will be reduced when the economy mode is active.

MODIFYING SCHEDULES



Scroll down to set or change the

Filter cycle Day, Start and Duration.

You can add schedules by scrolling

down (a) to Add, and selecting by

To modify a Water Care category, use the (middle right) lit button, to open the selected Water Care menu.

The menu screen is divided into two settings, Economy and Filter cycle with Economy being first. Set or change the Day, Start and Stop time if desired to keep the heater off (Economy mode).

using the (middle left) lit button.

To delete a schedule, press (top right) lit button.



You can modify the programmed schedules by selecting one (middle left) lit button and adjusting the schedule using the o o buttons. Press (middle left) lit button to move between parameters.

You have several possibilities for the schedule (Mon-Fri, weekend, every day, or single days). The schedules will be repeated every week. The time and duration are set in 30 minute increments. Once you have set the schedule, use (top left) lit button to go back. Ensure that you have selected the desired Water Care option in the main Water Care menu.

MAINTENANCE

From the Settings page you can access the Maintenance menu, which gives you access to the following options:

- · Maintenance reminders
- Standby

Use the O or O buttons to make a selection, and (middle left) lit button to select.



MAINTENANCE REMINDERS

The control panel will remind you of maintenance required on your **RECSPORT** Recreation System, like rinsing or cleaning the filter. Each task has its own duration, based on normal use.



The Maintenance reminders menu allows you to verify the time left

before maintenance is required. as well as to reset the time once a task is completed. Use the 🔘 or 🔾 buttons to move through the list.

To reset a task select it by pressing the (middle left) lit button, then confirm by pressing the lit button next to confirm when prompted. Once you have confirmed the task will be reset.

STANDBY

The Standby mode allows you to service your System. Pumps will stop for 30 minutes, and automatically restart after this time. Press (middle left) lit button to activate Standby mode.



Once Standby mode has been activated a screen will appear to

show that pumps are stopped. The normal page will return at the end of maintenance.

Press on the button next to cancel to leave Standby mode and restart the **RECSPORT** Recreation System.

DATE AND TIME

Here you can adjust the time format, change the year, date, and time. Use the O or O buttons to choose the setting that you want to adjust, and select it by pressing (middle left) lit button.



Use the 🔘 or 🕥 buttons to change the parameters, and 🥃

(middle left) lit button to move between parameters. Press (top left) lit button to take you back to the main Settings menu.

(top left)

KEYPAD SETTINGS

In this section, you can change the temperature unit, language, display orientation, rim around the control panel light color, and lock the control panel.

Use the or buttons to choose the setting that you want to adjust. Select it by pressing the



(middle left) lit button then use the o or buttons again to change the setting.

When you change the display orientation, the contextual options and or buttons adjust to the chosen orientation. The Audio and Setting buttons remain unchanged, as well as the jets and lights buttons in the home page.

Security settings allow you a Partial (Temperature) lock or Full (entire control panel) lock. Select Security screen by pressing the (middle left) lit button then use the or buttons to change to Full, Partial or Unlock. Press (top left) lit button to display an information screen telling you to press and hold button for 5 seconds to lock.

To unlock Full, press and hold (button for 5 seconds.

MISCELLANEOUS

You can turn the Warm weather mode ON or OFF. When ON the filtration pump will shut OFF whenever the water temperature gets 1°C (2°F) above the set point. Because of the Recreation system's large body of water it is recommended to keep the Warm weather mode OFF.



Press the (middle left) lit button, then use the o or buttons to change the Warm weather mode.

You can also hide some information on the home screen by selecting Hide in "Info messages" (not recommended).

ELECTRICAL CONFIGURATION

Please do not make changes in this section!

ABOUT

This section shows information about the control panel software number, and the revision numbers of the different components of your system.

SMART WINTER MODE

The Smart Winter Mode (SWM) is used to prevent water from freezing in the plumbing lines. As soon as there is a risk of freezing, this protection automatically kicks in. The SWM protection will turn back off only after 24 hours without a risk of freezing. During the SWM period, the Smart Winter Mode icon remains on; the icon blinks when the purge is active. The purge period indicates the amount of time between the purging of the plumbing lines based on the temperature behind the panels.



WI-FI IN.TOUCH 2 (OPTIONAL)

If your **RECSPORT** Recreation System is equipped with the Wi-Fi in.touch 2 module you will be able to use the internet or your home Wi-Fi network to control your **RECSPORT** Recreation System by downloading an App to your favorite devices. Use the instructions that came with your module or simply download the App to your device by searching "gecko in.touch 2" in your App store.

For more instructions go to: www.geckodocs. com/wireless and find the in.touch 2 TechBook or scan the QR code to the right.



This menu is only visible when the in.touch 2 module is installed.

Pressing the button illustrates that your **RECSPORT** Recreation System has the in.touch 2 system installed but DOES NOT indicate if your Wi-Fi is working with your **RECSPORT** Recreation System



AUDIO IN.STREAM 2 (OPTIONAL)

If your **RECSPORT** Recreation System has the optional in.stream 2 Bluetooth w/subwoofer system the following screens and functions will be available on the control panel:

AUDIO

The control panel is used with the in.stream 2 audio system. The Audio screen in the Settings menu gives you the option to disconnect your

Bluetooth enabled device, adjust the Fader, Balance or Sub Woofer.

Use the O or O buttons to scroll to desired option, press (middle left) lit button to select the function. Press the O or O buttons to change parameters. Press ((top left) lit button to take you back to the main Settings menu.



IN.STREAM 2 FUNCTIONS

Press the button in the home screen to access your audio system.

If you are using a device with Bluetooth technology, it must be connected for functions to work.

Please note that the Play/Pause and Change Track functions apply to devices using Bluetooth technology only, and will NOT work when AUX is selected as the source.

TURNING POWER ON/OFF

Press the (top right) lit button to start the audio on or off process.

SELECTING THE SOURCE

Press the
(top left) lit button to select a source using Bluetooth wireless technology



or AUX (aux is not available at time of publication). Selection will be indicated below In.stream 2.

PAIRING BLUETOOTH

Audio Power must be on. Go to the Bluetooth settings on your device and find in.stream 2 and press to connect. Enter pin 5555 and press pair to sync your device. **NOTE:** Only one device at a time can be synced.

PLAY/PAUSE AUDIO

Press the Play/Pause ((middle right) lit button to start or pause the audio. Press (middle left) lit button to mute or enable sound.

ADJUSTING THE VOLUME

Press the O or O buttons to increase or decrease the volume illustrated by the slider bar.

CHANGING TRACKS

Use the Last Track and Next Track (lower left) lit button or (lower right) lit button to change tracks.



TEMPERATURE CONTROL

The set temperature range is from 59°F to 99°F (15°C to 37.5°C). (The water temperature of any **RECSPORT** Recreation System may rise or lower slightly depending on the current use and condition of your **RECSPORT** Recreation System and on outside temperatures.)

The set temperature of the RECSPORT Recreation System water will automatically be 85°F (29.5°C) the first time power is applied. This is the setting programmed at the factory. After the **RECSPORT** Recreation System has been set up and used, the last temperature value set by the user will be stored in memory. If power is disconnected from the **RECSPORT** Recreation System, it will automatically revert to the last set temperature when power is reapplied.

To display the set temperature of the **RECSPORT** Recreation System:

Press the O or O buttons on the control panel in the home screen.

To increase the set temperature of the Recreation System:

Press the O button in the home screen. The set point will appear in blue. After 3 seconds without any change to the set temperature



value, the current water temperature will reappear in white.

To decrease the set temperature of the **RECSPORT** Recreation System:

Press the button in the home screen. The set point will appear in blue. After 3 seconds without any change to the set temperature value, the current water temperature will reappear in white.

JETS CONTROL

When pressed, the three buttons on the left of the screen will activate the jets when in the home screen. If left running the low or high speed pumps will automatically turn off after 2 hours.

HYDROMASSAGE JETS

Turn the hydromassage jet pump On to activate all of the hydromassage jets in the seated area as well as the waterfall if the waterfall valve is open. This pump has a low speed and high speed mode.

This jet pump will automatically turn on in low speed when the system is calling for heat or the filtration cycle.

Press jet button to activate the hydromassage jets in a low speed, you will see the jet 1 icon on the screen rotate slowly.

Press let button a second time to place the hydromassage jets in a high speed, you will see the jet 1 icon on the screen rotate faster.

Press jet button a third time to shut the hydromassage jets off.



SWIM JETS

The **RECSPORT** Recreation System uses a 2.5 Horsepower two speed pump to power the swim jets.

Press jet button to activate the jets (swim area) in a low speed, you will see the jet 2 icon on the screen rotate slowly.

Press jet button a second time to activate the jets in a high speed, you will see the jet 2 icon on the screen rotate faster.

Press iget button a third time to shut the swim jets off.

LIGHT CONTROL

All **RECSPORT** Recreation Systems are equipped with an interior lighting system. This system includes points of lights located throughout the **RECSPORT** Recreation System.

Press the ((lower right) button (when in the home screen) to activate interior lights and left light icon.

Press the (a) (lower right) button a second time to shut all interior lights off, when turning back on after several seconds the same light mode will appear.



Every time the light is turned off and on quickly a new light mode will appear.

The sequence is as follows: White, Aqua, Magenta, Azure, Amber, Emerald, Ruby, color wheel with abrupt color changes, slow full color wheel and fast full color wheel.

NOTE: If left on, the light will automatically turn off after 4 hours of operation.

EXTERNAL LIGHTS (OPTIONAL)

Press the (middle right) button (when in the home screen) to activate the external lights and right light icon. Press a second time to turn off.

FILTER CYCLES

When your **RECSPORT** Recreation System is first powered up, the default filter cycle is set to start at 12:00 pm and will run for 5 hours each day using the *Beginner* Water Care mode. Unless you set the time using the control panel (see Date & Time under Settings) the **RECSPORT** Recreation System filter cycle will start at power up and run for 5 hours and repeat every 24 hours.

We recommend setting your date and time first, then going to the Water Care section and making any desired changes for days, start times and length of time in the desired Water Care Mode.

The filter cycle will activate the hydromassage jets on low speed for the entire cycle that has been programmed.

NOTE: Power interruption of the **RECSPORT** Recreation System will not change the filter cycle settings when power is regained.

FILTER CYCLE SUSPENSION:

The filter cycle will be suspended every time a jet pump or light is activated manually during the filter cycle time. The suspension will end 10 minutes after the completion of the manual use.

POLLING

Polling is necessary for your **RECSPORT** Recreation System to maintain the proper set temperature. The temperature probe located inside the heating tube requires water from the hot tub to pass through it, this is done by automatically turning on your filtration pump for approximately 2 minutes. Outside temperatures will determine how often the pump is turned on, this can range anywhere from 15 to 90 minute intervals.

ALL OFF / MEMORY ON

Press the (1) (top right) button when in the home screen to turn the lights and any jets that are on OFF. It will not turn the music system off.

If you press this button again before pressing the light or jets button it will bring up the last settings before shutting off.



NOTE: The color of the lights will however advance to the next sequence.

Water Quality and Maintenance

BASIC INFORMATION

It's important to have clean water. Water maintenance is one of the least understood, yet most important areas of **RECSPORT** Recreation System ownership. Your dealer can guide you through the process of achieving and maintaining balanced water in your **RECSPORT** Recreation System, given your local conditions.

IMPORTANT: Water Terminology can be found at the end of this section.

- Always read & refer to the owner's manual for complete information.
- Test your water with a test strip once a week, or each time the RECSPORT Recreation System is used.
- Add chemicals in frequent, small amounts to prevent overdosing the RECSPORT Recreation System.
- Use the RECSPORT Recreation System only when the chlorine level is between 1-5 ppm or manually add chlorine as needed.
- It is the RECSPORT Recreation System owner's responsibility to prevent over or under chlorination.

IMPORTANT: It is recommended at a minimum to change 50% of your water every year; however, it is dependent on the amount of usage. Check with your **ENDLESS POOLS** dealer to determine if water in your region has unique qualities - such as high metal or mineral content - that should be addressed.

WATER QUALITY CHART

PARAMETER	TARGET	MIN - "OK" RANGE - MAX					
pН	7.4	7.2	7.8				
ALKALINITY	100 ppm	80 ppm	120 ppm				
HARDNESS	100 ppm	75 ppm	150 ppm				
CHLORINE	3 ppm	1 ppm	5 ppm				

Maintaining the water quality and the cleanliness of the filters in your RECSPORT Recreation System is your responsibility. Keeping the RECSPORT Recreation System water balanced prolongs the life of the components and will make the water more comfortable. Your program will depend on your water's mineral content, how often you use your RECSPORT Recreation System, and how many people use it. Watkins Wellness has developed several water care systems and products to simplify water care which are available from authorized ENDLESS POOLS dealers.

CHEMICAL SAFETY

When using chemicals, read the labels carefully and follow directions precisely. Though chemicals protect you and your **RECSPORT** Recreation System when used correctly, they can be hazardous in concentrated form. Always observe the following guidelines:

- Allow only a responsible person to handle RECSPORT Recreation System chemicals. Keep them out of the reach of children.
- Accurately measure the exact quantities specified, never more. Do not overdose your RECSPORT Recreation System.

- Handle all containers with care. Store in a cool, dry, well ventilated place.
- Always keep chemical containers closed when not in use. Replace caps on their proper containers.
- Don't inhale fumes, or allow chemicals to come in contact with your eyes, nose, or mouth. Wash your hands immediately after use.
- Follow the emergency advice on the product label in case of accidental contact, or if the chemical is swallowed. Call a doctor or the local Poison Control Center. If a doctor is needed, take the product container along with you so that the substance can be identified.
- Don't let chemicals get on surrounding surfaces or landscaping. Don't use a vacuum cleaner to clean up chemical spills.
- · Never smoke around chemicals. Some fumes can be highly flammable.
- Don't store any chemicals in the RECSPORT Recreation System equipment compartment.

HOW TO ADD CHEMICALS TO THE WATER

IMPORTANT: All **RECSPORT** Recreation System water chemicals, must always be dispersed into the swim area while all jet pumps are running on high, and must run for a minimum of ten minutes.

TO ADMINISTER **RECSPORT** RECREATION SYSTEM WATER CHEMICALS:

- Fold back the cover.
- 2. Turn both jets systems ON, run for 10 minutes and turn OFF.
- Carefully measure the recommended amount of chemical and disperse into swim area while jets are on. Use care not to splash chemicals on your hands, in your eyes, on the RECSPORT Recreation System sheet surface, or on the siding.
 Risk of Drowning: Never leave an open RECSPORT Recreation System unattended!

IMPORTANT "SUPER CHLORINATION/NON-CHLORINE SHOCK TREATMENT" NOTE: After administering a super chlorination treatment or non-chlorine shock to your **RECSPORT** Recreation System, leave the cover open for a minimum of 20 minutes to allow the oxidizer gas to vent. A high concentration of trapped oxidizer gas which may exist as a result of the shock treatment (not daily sanitation) may eventually cause discoloration or vinyl degradation to the bottom of the cover.

FUNDAMENTALS OF WATER MAINTENANCE

Testing: Test the water weekly or each time the RECSPORT
Recreation System is used with convenient test strips or more accurate
liquid/tablet reagent test kit per instructions. Critical parameters:
sanitizer level, pH, Calcium Hardness (CH), and Total Alkalinity (TA).
Store test equipment in a dark, cool, dry place to maintain potency.

- Chemical Balance/pH Control: It is important to adjust the primary water parameters (Total Alkalinity, Calcium hardness, pH) into the recommended ranges so that they are stabilized or balanced. Balance the water chemistry every time you fill the RECSPORT Recreation System with new water and then during the life of that body of water. Keeping the water in balance prevents damage by holding the pH in a safe range and preventing calcium scale formation on RECSPORT Recreation System equipment. A low pH can damage metal components whereas a high pH can cause high levels of calcium to form scale. Your dealer should provide a detailed water chemistry orientation soon after your new RECSPORT Recreation System is filled for the very first time.
- The following three water components must be kept in balance to avoid damage to the RECSPORT Recreation System. Do balance these components in the order they are listed here as each will help you balance the next using a minimum amount of chemicals.
- ALKALINE ADD pH WATER DECREASER 8.2 (SCALING TO LOWER ZONE) COMFORT ZONE **IDEAL** ACIDIC ADD pH WATER **INCREASER** 6.8 (CORROSIVE TO RAISE ZONE) нα
- Calcium Hardness (CH)
 CH is the measure of the amount of dissolved
- calcium in the water. Low levels can make the water corrosive and high levels cause scale formation on **RECSPORT** Recreation System components. The recommended CH reading is between **75 150 ppm**. If the CH level is too high, lower it with the calcium remover per instructions. Once in balance, the CH reading normally remains stable until more water is added. Great care must be taken when filling the **RECSPORT** Recreation System from a water softener to ensure that the calcium remains in balance and avoid damage to the **RECSPORT** Recreation System.
- 2. Total Alkalinity (TA) TA is a measure of the water's ability to resist changes of pH or buffer capacity. A low TA allows the pH to fluctuate easily. The recommended TA reading is between 80 120 ppm. To raise the TA, use pH/Alkalinity Up (sodium hydrogen carbonate). To lower the TA, use pH/Alkalinity Down (sodium bisulfate). We recommend you check the TA reading once per month. Raising/lowering the TA may cause the pH readings to fluctuate widely. Ignore the pH readings on the test strip while you are balancing the TA.
- 3. pH The pH is the measure of the acidity and alkalinity. Maintaining the proper pH level will optimize the effectiveness of the sanitizer, preventing damage to the RECSPORT Recreation System and physical discomfort for RECSPORT Recreation System users. A low pH dissipates sanitizer, causes corrosion, and irritates RECSPORT Recreation System users. A high pH level will neutralize sanitizer, promote scaling and cloud water. The recommended pH reading is between 7.2 7.8. To lower the pH level, use pH/Alkalinity Down (sodium bisulfate). To raise the pH level, use pH/Alkalinity Up (sodium carbonate).
- Water Conditioners: RECSPORT Recreation System fill water varies from location to location and user to user, therefore it is important to consult with your dealer for an appropriate program.
 - a. CLEAN SCREEN pre-filter –The CLEAN SCREEN pre-filter should be used at every fill and top-off to remove contaminants from the fill water, especially iron, copper, and manganese. Many water sources, including well water, contain high concentrations of minerals that can cause staining of the shell and plastics.

- b. Stain and Scale control For water high in calcium and minerals, it may be necessary to use an anti-scalant like Stain and Scale control. As water evaporates from your RECSPORT Recreation System and new water is added, the amount of dissolved minerals like calcium, copper, iron, and manganese will increase. (Minimize evaporation by keeping the cover on the RECSPORT Recreation System whenever possible.) High iron or copper content in the water may produce green or brown stains on the RECSPORT Recreation System.
- c. Foam Inhibitors Soap is introduced into the RECSPORT Recreation System water from users' bodies and swimming apparel and can cause the RECSPORT Recreation System water to foam when the jets are used. Low levels of calcium hardness (soft water) can increase foaming. Although ozone can oxidize soap residual, it may become necessary to add Foam Inhibitors to suppress the foam. Excessive soap in the water may require a water change to resolve.
- Oxidizers: Ozone and Monopersulfate (MPS) are oxidizers used to
 prevent the buildup of contaminants, maximize sanitizer efficiency,
 minimize combined chlorine, and improve water clarity. They are to
 be used in conjunction with EPA registered sanitizers. Chlorine-Free
 Oxidizer, Monopersulfate (MPS) is a granular oxidizing chemical.
- Sanitizers: Maintaining the recommended residual level of an EPA registered sanitizer at all times will decrease the occurrence of unsafe bacteria and viruses in your RECSPORT Recreation System water. The recommended Free Available Chlorine (FAC), the amount of available chlorine sanitizer, is 1 5 ppm. A low FAC can allow bacteria and viruses to grow rapidly in the warm water, and a high FAC can cause discomfort to the user's eyes, lungs, and skin. Each sanitizer carries its own instructions regarding how much to use and when to add it to the RECSPORT Recreation System water. Consult your dealer for their recommendations and instructions on proper sanitizing of the RECSPORT Recreation System.

Watkins Wellness recommends the following sanitizer:

- Sodium Dichloro-s-Triazinetrione (sodium dichlor or chlorine)
- · Biguanide
- Liquid sodium hypochlorite (do not use splashless)

WARNING: DO NOT use tri-chlor chlorine, bromo-chloro-dimethyl-hydantoin (BCDMH), or any type of compressed bromine or chlorine, acid or any type of sanitizer which is not recommended by Watkins Wellness.

THE ENDLESS POOLS WATER MAINTENANCE PROGRAM

FILLING THE **RECSPORT** RECREATION SYSTEM WITH WATER

Use the **CLEAN SCREEN** pre-filter to remove unwanted contaminants such as rust, dirt, detergents, and algae from the fill water. Dissolved metals, copper, iron, and manganese are also removed. Instructions are included with the **CLEAN SCREEN** pre-filter. Always fill the **RECSPORT** Recreation System through the filter compartment. Do not fill your **RECSPORT** Recreation System using water from a swimming pool as pool chemicals are very different from those used in a **RECSPORT** Recreation System and can damage your **RECSPORT** Recreation System.

ADDING CHEMICALS TO THE WATER

All **RECSPORT** Recreation System water chemicals, must always be dispersed directly into the swim area while all jet pumps are running in the high speed mode, and it must run for a minimum of ten minutes with the covers off.

BUILDING A SANITIZER ROUTINE

During the first month of ownership, measure the sanitizer residual daily in order to establish a baseline of sanitizer needed vs. **RECSPORT** Recreation System usage. Sanitizer needed is the amount of Free Available Chlorine needed to accommodate the number of users and their combined usage time. For example, two **RECSPORT** Recreation System users for twenty minutes every day creates regular demand on the sanitizer that is used to determine how much sanitizer to add in order to maintain the proper residual. If the usage pattern increases dramatically with invited guests, the amount and frequency of sanitizer required will also increase.

PERFORMING SUPER CHLORINATION/ NON-CHLORINE SHOCK TREATMENT

A weekly or monthly super chlorination (1.5 tsp dichlor/250 gal or 950 liters) or shock (4tbs mps/250 gal or 950 liters) may be required of your chosen sanitation program. Increasing chlorine to 5 ppm for 24-48 hours removes excess waste and chloramines from the water. Sodium dichlor is 6x stronger than MPS and may be more appropriate for those users that experience heavy bather load conditions. Operate all jets and leave the cover open for a minimum of 20 minutes to allow the oxidizer gas to vent to prevent damage and discoloration to the cover and pillows after administering a super chlorination or shock to your **RECSPORT** Recreation System. This type of damage is considered chemical abuse and is not covered under the terms of the limited warranty.

IMPORTANT: Always allow the Free Available Chlorine to fall below 5 ppm before using your **RECSPORT** Recreation System.

DANGER: Never leave an open RECSPORT Recreation System unattended, especially if there are children present!

USING SILVER ION

Silver ions are introduced into the water via erosion of silver infused beads which inhibits bacteria growth. When combined with MPS, or chlorine, waste is oxidized and removed from the water. It is important to follow the recommended application and maintenance programs outlined for the product's use. If the **RECSPORT** Recreation System is

being used over an extended period of time, such as a whole afternoon or evening, additional sanitizer will be needed.

Required:

- a. One Silver Ion cartridge per 500 gallons (1,893 liters).
- Silver lon cartridges to be placed inside filter skimmer tray (maximum of 2 per tray).
- c. Weekly Super Chlorinate/Shock the RECSPORT Recreation System to reactivate the silver ion cartridge, allow the release of silver ions, and quickly destroy any remaining contaminants. Without this weekly shock treatment, the silver ion cartridge may stop releasing silver ions into the water.

IMPORTANT: Use only Dichlor sanitizer. Silver is not compatible with bromine and biguanides. Don't use a water clarifier. Clarifiers will cause the water to become cloudy.

MANUAL CHLORINE (SODIUM DICHLOR)

Watkins Wellness recommends the use of Concentrated Chlorinating Granules (sodium dichlor) for sanitizing the water. Sodium dichlor is preferred because it is totally soluble, dissolves quickly, and is nearly pH neutral. The recommended Free Available Chlorine (FAC), the amount of available chlorine sanitize the **RECSPORT** Recreation System, 1.0-5.0 ppm.

If the FAC is too low: Increase the FAC by adding granulated sodium dichlor.

If the FAC is too high: Allow time to pass and the FAC level will naturally drop over time.

If the RECSPORT Recreation System smells of chlorine: super chlorinate or shock the RECSPORT Recreation System FAC chlorine does not have an odor whereas combined spent chlorine (chloramines) has a strong chlorine odor that can be eliminated by shocking the water.

IMPORTANT: There are several forms of stabilized chlorine available for use in RECSPORT Recreation Systems and swimming pools. It is extremely important to choose one specifically designed for RECSPORT Recreation Systems. Use of an incorrect product such as tri-chlor which has a very low pH (2.6) and dissolves too quickly in hot water, results in extremely high levels of chlorine that WILL cause damage to your RECSPORT Recreation System. Use of a liquid or compressed bromine/chlorine or unapproved sanitizer WILL damage your RECSPORT Recreation System and is specifically not covered under the terms of the limited warranty.

DO:

- Disperse all chemicals slowly into the swim area with the jet pumps operating for ten minutes.
- Use special care if using baking soda to clean either the interior or exterior plastic surfaces.

IMPORTANT: Watkins Wellness DOES NOT recommend the use of any floating chemical dispenser. Damage to the **RECSPORT** Recreation System shell or components caused by a floating chemical dispenser is specifically not covered under the terms of the limited warranty. Floating dispensers can become trapped in one area and cause an over-sanitization or release large chunks of sanitizer that very quickly chemically burn the shell and cover.

DON'T:

- · Use compressed sanitizers.
- Use a floater type sanitization system as a low or no maintenance solution to your RECSPORT Recreation System maintenance program.
- Use a sanitizer which is not designed for RECSPORT Recreation Systems.
- Broadcast or sprinkle the chemicals onto the water surface without the swim jets running during chemical additions and any additional 10 minutes after dose. This method may cause chemically-induced RECSPORT Recreation System surface blistering (chemical abuse).

OZONE MAINTENANCE

Reduced or no ozone bubbles coming from heater return (clogged ozone injector) or no ozone, clean the injector:

- 1. Place 16 ounces (0.5 liter) of white vinegar into a cup or bucket.
- Carefully loosen the long tubing attached to the bottom of the ozonator, located in the equipment compartment.

DANGER: Place the end of the tubing into the vinegar, making certain that the end of the tubing sits at the bottom of the container.

- Run the spa until all 16 ounces (0.5 liter) of the vinegar are gone.
 This should allow an ample flow of vinegar to be run through the injector and clear the blockage.
- Reinstall the tubing to the bottom of the ozonator.

VACATION WATER CARE INSTRUCTIONS

If you plan to be away from home, follow these instructions to ensure that the water quality of your **RECSPORT** Recreation System is maintained:

SHORT TIME PERIODS (3-5 DAYS):

- 1. Adjust the pH by following the instructions outlined in the Water Quality and Maintenance section.
- Sanitize the water by following the shock procedures also listed in the Water Quality and Maintenance section.
- 3. Lock your cover in place using the coverlocks.
- Set Water Care Mode to Away from Home (pg.10).
- 5. Upon your return, sanitize the water by following the shock procedures, and balance the pH.

LONG TIME PERIODS (5-14 DAYS):

Prior to leaving:

- At least one day before you leave, set Water Care Mode to Away.
 IMPORTANT: RECSPORT Recreation System water oxidizers such as sodium dichlor (chlorine) maintain their level of effectiveness substantially longer in cool water 59°F (15°C) than in hot water 97°F to 99°F (36°C 37.5°C).
- Adjust the pH as required. Sanitize the water by following the shock procedures.

Upon your return:

Sanitize the water by following the shock procedures. Return the set temperature to its original setting. The RECSPORT Recreation System water will be safe for you to use once the Free Available Chlorine residual level has dropped below 5.0 ppm.

IMPORTANT: If you will not be using your **RECSPORT** Recreation System for an extended period of time (in excess of 14 days) and an outside maintenance service (or neighbor) is not available to assist with the water maintenance, draining or winterizing of the **RECSPORT** Recreation System is recommended.

SUPPLEMENTAL WATER MAINTENANCE

Proper water sanitation and mineral balance (pH control) are absolutely essential for a complete **RECSPORT** Recreation System water maintenance program. Here are two other popular water additives that are optional:

Mineral Deposit Inhibitors

As water evaporates from your **RECSPORT** Recreation System and new water is added, the amount of dissolved minerals will increase. (Minimize evaporation by keeping the cover on the **RECSPORT** Recreation System whenever possible.) The **RECSPORT** Recreation System water may eventually become "hard" (Calcium Hardness too high) enough to damage the heater by calcifying its surface. Proper pH control can minimize this.

Occasionally, high iron or copper content in the water may produce green or brown stains on the **RECSPORT** Recreation System. A stain and scale inhibitor may help to reduce these metals.

IMPORTANT: Well water may contain high concentrations of minerals. The use of a low water volume, extra-fine pore water filter (in-line pre-filter such as the **CLEAN SCREEN** pre-filter) will help to remove many of the larger particles during the filling of the **RECSPORT** Recreation System. In-line pre-filters can be purchased at your local **ENDLESS POOLS** dealer.

Foam Inhibitors

RECSPORT Recreation System water requires changing due to the buildup of soap in the water. Typically, soap will cause the **RECSPORT** Recreation System water to foam when the jets are used. Soap is introduced into the **RECSPORT** Recreation System water from two sources: users' bodies, which retain a soap residual after showering, and swimming apparel, which retains soap after washing.

Foam inhibitors can suppress foam, but cannot remove soap from the water. Soap is very difficult to remove from the water because soap is not oxidized by any chemical added to the **RECSPORT** Recreation System. Only ozone can oxidize soap. Eventually the soap build-up in the water will be concentrated, resulting in an unclean feeling on the bather's skin, which is impossible to remedy. When this occurs, it's time to drain and refill the **RECSPORT** Recreation System.

GLOSSARY

The following chemical terms are used in this Water Quality and Maintenance section. Understanding their meaning will help you to better understand the water maintenance process.

Bromamines: Compounds formed when bromine combines with nitrogen from body oils, urine, perspiration, etc. Unlike chloramines, bromamines have no pungent odor, and are effective sanitizers.

Bromine: A halogen sanitizer (in the same chemical family as chlorine). Bromine is commonly used in stick, tablet, or granular form however, stick and tablet form should NOT be used.

Calcium Hardness: The amount of dissolved calcium in the RECSPORT Recreation System water. This should be approximately 75 -150 ppm. High levels of calcium can cause cloudy water and scaling. Low levels can cause harm to the RECSPORT Recreation System equipment.

Chloramines: Compounds formed when chlorine combines with nitrogen from body oils, urine, perspiration, etc. Chloramines can cause eye irritation as well as having a strong odor. Unlike bromamines, chloramines are weaker, slower sanitizers.

Chlorine: An efficient sanitizing chemical for **RECSPORT** Recreation Systems. Watkins Wellness recommends the use of sodium dichlor-type granulated chlorine or liquid sodium hypochlorite.

Chlorine (or Bromine) Residual: The amount of chlorine or bromine remaining after chlorine or bromine demand has been satisfied. The residual is, therefore, the amount of sanitizer which is chemically available to kill bacteria, viruses and algae.

Corrosion: The gradual wearing away of metal and plastic **RECSPORT** Recreation System parts, usually caused by chemical action. Generally, corrosion is caused by low pH or by water with levels of TA, CH, pH or sanitizer which are outside the recommended ranges.

Halogen: Any one of these five elements: fluorine, chlorine, bromine, iodine, and astatine.

MPS: Monopersulfate is a non-chlorine oxidizer.

Nitric Acid: The formulation of nitric acid, a highly corrosive chemical, is a byproduct of the ozone generating process. Nitric acid is produced in very small quantities and is readily dissolved in the water stream with ozone.

Oxidizer: The use of an oxidizing chemical is to prevent the buildup of contaminants, maximize sanitizer efficiency, minimize combined chlorine and improve water clarity. See MPS and Ozone.

Ozone: Ozone is a powerful oxidizing agent which is produced in nature and artificially by man. Ozone forms no byproducts, oxidizes chloramines, and will not alter the water's pH.

pH: The measure of the **RECSPORT** Recreation System water's acidity and alkalinity. The recommended pH for the **RECSPORT** Recreation System water is 7.2 to 7.8. Below 7.0 (considered neutral), the **RECSPORT** Recreation System water is too acidic and can damage the heating system. Above 7.8, the water is too alkaline and can result in cloudy water, and scale formation on the shell and heater.

ppm: The abbreviation of "parts per million", the standard measurement of chemical concentration in water. Identical to mg/l (milligrams per liter).

Reagent: A chemical material in liquid, powder, or tablet form for use in chemical testing.

Sanitizer: Sanitizers are added and maintained at recommended residuals to protect bathers against pathogenic organisms which can cause disease and infection in **RECSPORT** Recreation System water.

Scale: Rough calcium-bearing deposits that can coat **RECSPORT** Recreation System surfaces, heaters, plumbing lines, and clog filters. Generally, scaling is caused by mineral content combined with high pH. Additionally, scale forms more readily at higher water temperatures.

Sodium Hypochlorite (Liquid chlorine/bleach): Unstabilized (without cyanuric acid) chlorine in liquid form. Very effective however it has a very high pH and requires acid adjustment to maintain water parameters. Never add acid directly to chlorine.

Super-Chlorination: Also known as "shock treatment." Super-Chlorination is a process of adding significant doses of a quick dissolving sanitizer ("dichlor" is recommended) to oxidize non-filterable organic waste and to remove chloramines and bromamines.

Total Alkalinity (TA): The amount of bicarbonates, carbonates, and hydroxides present in **RECSPORT** Recreation System water. Proper total alkalinity is important for pH control. If the TA is too high, the pH is difficult to adjust. If the TA is too low, the pH will be difficult to hold at the proper level. The desired range of TA in **RECSPORT** Recreation System water is 80 to 120 ppm.

CARE AND MAINTENANCE

Your **ENDLESS POOLS RECSPORT** Recreation System is manufactured from the highest quality, most durable materials available. Even so, the **RECSPORT** Recreation System care and maintenance program you develop will ultimately determine how long your **RECSPORT** Recreation System, and its individual components, will last. Regular maintenance and following the advice in this section will help you to protect your investment.

FILTER MAINTENANCE

At least once a week, check and clean the skimmer tray to ensure proper filter flow. Remove leaves, foreign matter, and debris. It is very important to keep your **RECSPORT** Recreation System filter cartridges clean and free of particles to ensure proper water flow. Clean filters enables the hydrotherapy system to function properly and allows for more efficient filter cycles. Depending on how frequently your **RECSPORT** Recreation System is used, we recommend cleaning the **RECSPORT** Recreation System filter cartridges every four weeks. If this is not done, the filter may clog and restrict water flow, which causes improper filtration, poor jet performance and may possibly freeze.

IMPORTANT: The frequency and duration of use, and the number of occupants all contribute to determining the appropriate time between filter cleanings. More use means that more frequent filter cleanings will be required.

FILTER CARTRIDGE REMOVAL AND CLEANING INSTRUCTIONS

Place the RECSPORT Recreation System in the "Standby" mode, then proceed as follows:

 Find the filter grate inside the RECSPORT Recreation System.



 Pull the filter grate from the bottom up until it unlocks from the wall.
 IMPORTANT: ONLY PULL FILTER GRATE UP SLIGHTLY.



Pull filter grate away from wall and set aside.



4. Pull skimmer tray away from wall, remove and clean.



 To remove the filter, turn using the handle in the center of the filter counter-clockwise.



 Pull filter up, then angle the top away from the filter compartment to pull filter completely out. Each filter has 50 sq. feet of effective filter area.



 Repeat steps 4 & 5 to remove second filter. Always clean the filter using a filter degreaser to remove mineral and oil buildup. Simply soak the filter in the degreaser (according to the



package directions), then place the filter on a clean surface and spray until clean using a garden hose. It may be necessary to rotate the filter while spraying to remove any debris lodged between the filter pleats.

- 8. Re-insert filter cartridge by reversing steps 5, 6 & 7.
- 9. Slide skimmer try back into filter compartment reversing ste p 4.
- Position filter grate as seen in step 2 & 3, grate should touch wall
 of RECSPORT Recreation System slightly above black filter
 equipment compartment tracks. Slide filter grate down until it stops.

NOTE: Replacement filter cartridges are available from your **ENDLESS POOLS** dealer. Refer to the back of this manual to determine the appropriate size for your **RECSPORT** Recreation System.

DRAINING YOUR RECSPORT RECREATION SYSTEM

Turn off the GFCI breaker in sub-panel, or main electrical panel.

 Locate the drain valve (bottom, lower right of control panel) for the RECSPORT Recreation System.

Pull on handle (Figure 1, pliers may be used to pull handle) until you reach the mid position then rotate handle slightly to fully extended drain tube (drain cap and 1" (2.5 cm) of the drain tube is exposed) (Figure 2) then remove the drain cap (Figure 3).

NOTE: Do not remove drain cap in mid position. Attach the garden hose to the end of the drain (to avoid flooding of the foundation surrounding the RECSPORT Recreation System) making sure not to push the drain tube inward. Route the outlet of the hose to an appropriate draining area.


NOTE: RECSPORT Recreation System water with a high sanitizer level may harm plants and grass.


 Push the garden hose and drain tube half-way back towards the RECSPORT Recreation System





IMPORTANT: All models will drain almost completely through the drain valve. Equipment such as the jet pump and heating system may not completely drain. Any water remaining within the plumbing or equipment after draining will only need to be removed if the **RECSPORT** Recreation System is being winterized.

- After your RECSPORT Recreation System is empty, clean the shell and filter cartridges.
- Pull and remove garden hose, replace drain cap and push drain tube back into RECSPORT Recreation System as seen in Figure 1.
- Follow the "START-UP PROCEDURES" to refill your RECSPORT Recreation System.









WINTERIZING YOUR RECSPORT RECREATION SYSTEM

An ENDLESS POOLS RECSPORT Recreation System may be used year round, even in colder climates. If you will not be using the RECSPORT Recreation System during the winter in an area where freezing is a problem, special consideration must be taken to protect the pool and auxiliary equipment if either is located outside. If you have any questions regarding precautions to take against freezing, please call our Customer Service Department at (800) 999-4688 (extension 8432) or e-mail customerservice@watkinsmfg.com.

CARE OF THE PILLOWS

The RECSPORT Recreation System pillows will provide years of comfort if treated with care. They have been positioned above the water level to minimize the bleaching effects of chlorinated water and other RECSPORT Recreation System water chemicals. To extend their life, whenever the RECSPORT Recreation System shell is being cleaned, the RECSPORT Recreation System pillows should be removed and cleaned. Body oils can be removed with a mild soap and water solution. ALWAYS rinse off the RECSPORT Recreation System pillows thoroughly to remove any soap residue. If the RECSPORT Recreation System is not going to be used for a long period of time (that is during a vacation or if the RECSPORT Recreation System is winterized), or when the RECSPORT Recreation System water is being super-chlorinated, the RECSPORT Recreation System pillows should be removed until the next use of the RECSPORT Recreation System.

TO REMOVE AND REPLACE THE PILLOWS:

- Carefully lift one end of the pillow away from the RECSPORT Recreation System shell.
- Continue lifting one end until all pillow retainers are released from the pillow.
 - **IMPORTANT**: Just pulling the pillow straight up and out of the shell recess will eventually damage the pillow. This abuse is not covered under warranty.
- To reinstall the RECSPORT Recreation System pillow, carefully bend the pillow slightly to allow one of the pillow retainers to slip into the recess in the back of the pillow.
- Keeping the pillow slightly bent, slide the other pillow retainer into the recess in the back of the pillow.
- After all the pillow retainers are in place, press the pillow down into the recess in the RECSPORT Recreation System shell.

CARE OF THE EXTERIOR

RECSPORT RECREATION SYSTEM SHELL

Your ENDLESS POOLS RECSPORT Recreation System has an acrylic shell. Stains and dirt generally will not adhere to your RECSPORT Recreation System's surface. A soft rag or a nylon scrubber should easily remove most dirt. Most household chemicals are harmful to your RECSPORT Recreation System's shell (see below for detailed information on cleaning agents). Always rinse off any RECSPORT Recreation System shell cleaning agent with fresh water.

IMPORTANT:

- 1. The following products are the ONLY approved cleaning agents for your ENDLESS POOLS RECSPORT Recreation System shell: plain water, Spa Shine, or Soft Scrub[®]. The use of alcohol or any other household cleaner other than those listed to clean the RECSPORT Recreation System shell surface is NOT recommended. DO NOT use any cleaning products containing abrasives or solvents since they may damage the shell surface, specifically: Simple Green[®], Windex[®] or Spa Mitt. NEVER USE HARSH CHEMICALS! Damage to the shell by use of harsh chemicals is not covered under the warranty. Always rinse off any RECSPORT Recreation System shell cleaning agent with fresh water.
- Iron and copper in the water can stain the RECSPORT Recreation System shell if allowed to go unchecked. Ask your ENDLESS POOLS dealer about a Stain and Scale Inhibitor to use if your RECSPORT Recreation System has a high concentration of dissolved minerals. (Watkins Wellness recommends Stain & Scale Defense).
- Keep all cleaners out of the reach of children and use care when applying.

RECSPORT RECREATION SYSTEM CABINET

All **RECSPORT** Recreation Systems use the exclusive all-climate cabinet designed for years of performance. The unique design is made from a rigid polymer for durability and adds a film finish that provides a rich appearance.

Cleaning consists of simply spraying the cabinet with a mild soap and water solution to remove any stains and residue.

Do not rub the cabinet with an abrasive material or use abrasive cleaners as this may damage its surface.

VINYL COVER (OPTIONAL)

The vinyl cover is an attractive, durable foam insulation product. Monthly cleaning and conditioning are recommended to maintain its beauty.

To clean and condition the vinyl cover without a lifter:

- Remove the covers from the RECSPORT Recreation System and gently lean against a wall or fence.
- With a garden hose, spray the covers to loosen and rinse away dirt or debris.
- Using a large sponge and/or a soft bristle brush, and using a very mild soap solution (one teaspoon dishwashing liquid with two gallons of water), or baking soda (sodium bicarbonate), scrub the vinyl top in a circular motion. Do not let the vinyl dry with a soap film on it before it can be rinsed clean.
- 4. Scrub the cover's perimeter and side flaps. Rinse clean with water.
- Rinse off the underside of the cover with water only (use no soap), and wipe it clean with a dry rag.
- IMPORTANT: To remove tree sap, use cigarette lighter fluid (not charcoal lighter fluid). Use sparingly, and rinse with a saddle soap solution immediately afterwards, then wipe dry.

SERVICE INFORMATION

GENERAL INFORMATION

Your ENDLESS POOLS RECSPORT Recreation System has been designed to provide years of trouble-free use. As with any appliance, problems may occasionally occur that require the expertise of a qualified service person. Though such simple repairs as resetting a GFCI switch or breaker, or resetting a high limit thermostat may not require a service call, they may indicate that a more serious condition exists. These conditions may require an experienced service person. Before calling for service, please refer to the Troubleshooting Guide. Always retain your original sales receipt for future reference.

GFCI AND HIGH LIMIT THERMOSTAT

If your **RECSPORT** Recreation System fails to operate at any time, first check the power supply to the **RECSPORT** Recreation System.

Check the GFCI breaker in the subpanel. If a GFCI has tripped, reset it. If it will not reset, this may be an indication of a ground fault (short circuit) within the electrical components. Contact an Authorized Service Technician for a complete diagnosis.

If upon checking the GFCI you find that it has not tripped, check the house breaker panel and ensure the main breaker for the electrical circuit supplying the **RECSPORT** Recreation System has not tripped. If it has, this is an indication that the circuit was either overloaded or a ground fault exists between the breaker panel and the **RECSPORT** Recreation System receptacle or subpanel. Contact a qualified electrician.

If upon checking the main house breaker and **RECSPORT** Recreation System GFCI you find no failures, check the high limit thermostat. To check it, simply turn off power to the **RECSPORT** Recreation System for 30 seconds. This will automatically reset the high limit thermostat if it has tripped. If the **RECSPORT** Recreation System energizes once you turn the power back on, this indicates reduced water flow through the heating system. Tripping of the high limit thermostat is normally a result of one or a combination of these problems. 1) clogged filter cartridge(s), 2) blockage within the system plumbing, 3) a non-functioning heater circulation pump, 4) power was not disconnected from the **RECSPORT** Recreation System before it was drained, 5) an air lock in the plumbing lines. (The Power Indicator on the front of the **RECSPORT** Recreation System's control panel will also be blinking if the high limit thermostat circuit has tripped.)

If the **RECSPORT** Recreation System does not function after tripping and resetting the GFCl's or resetting the high limit thermostat, then the problem should be referred to an Authorized Service Technician. Refer to the Troubleshooting Guide for additional service information.

MISCELLANEOUS SERVICE INFORMATION

The control and high-limit thermostats are equipped with electronic sensors that are connected to the **RECSPORT** Recreation System's plumbing. Never cut or kink the wires that connect the sensors to the thermostats within the control box.

The jet pump is equipped with a thermal overload cutoff switch that is designed to protect the pump from overheating. If the pump shuts itself off in an older **RECSPORT** Recreation System, it could indicate failure of the pump motor bearings. If the pump shuts itself off in a new **RECSPORT** Recreation System, it is usually the result of one or a combination of the following factors:

- Thermal overload: Although mass-produced, not all thermal overload cutoffs are exactly the same. Some are more sensitive than others and will shut the pump off at lower temperatures.
- High temperature: All ENDLESS POOLS RECSPORT Recreation System models are equipped with a jet pump shroud that vents the heat generated by the pump motor to the outside of the equipment compartment, and back into the RECSPORT Recreation System water. If the vent is blocked by masonry, grass or debris, overheating of the jet pump may occur. Once the pump motor has cooled sufficiently and any blockage has been removed from the vent opening, the jet pump can be restarted.
- Friction: Sometimes the moving parts of a new pump are tight enough to cause heat build-up due to friction. After a normal break-in period, the pump will run cooler.
- Improper wiring: If the RECSPORT Recreation System is connected with an extension cord, and/or the house wiring is undersized, the pump may starve for voltage and therefore may draw more amperage and generate excessive heat.
- If the pump is shutting down due to excessive heat, make sure the
 equipment compartment has adequate ventilation. The air gap at the
 bottom must not be blocked. Should your jet pump continue to shut off
 after short periods of use, contact a qualified service technician.

ACTS INVALIDATING WARRANTY

The limited warranty is void if the ENDLESS POOLS RECSPORT Recreation System has been improperly installed, subjected to alteration, misuse, or abuse, or if any repairs on the RECSPORT Recreation System are attempted by anyone other than an authorized representative of Watkins Wellness. Alteration shall include any component or plumbing change, electrical conversion, or the addition of any non-approved sanitation or water purification device or heating system which contributes to component or unit failure or unsafe operating system. Misuse and abuse shall include any operation of the **RECSPORT** Recreation System other than in accordance with Watkins Wellness printed instructions, or use of the **RECSPORT** Recreation System in an application for which it is not designed; specifically: use of the RECSPORT Recreation System in a non-residential application; damage caused by operation* of the RECSPORT Recreation System at water temperatures outside the range of 35°F - 120°F (1.5°C - 49°C); damage caused by a dirty, clogged or calcified filter cartridge; damage to the **RECSPORT** Recreation System surface caused by the use of tri-chloro chlorine, BCDMH, misuse of chemical tablets in a floater, acid, or any other RECSPORT Recreation System chemicals or **RECSPORT** Recreation System surface cleaners which are not recommended by Watkins Wellness; damage caused by allowing undissolved **RECSPORT** Recreation System sanitizing chemicals to lie on the **RECSPORT** Recreation System surface (no **RECSPORT** Recreation System surface material can withstand this kind of abuse); damage to components or RECSPORT Recreation System surface caused by improper water chemistry maintenance; and damage to the **RECSPORT** Recreation System surface caused by leaving the **RECSPORT** Recreation System uncovered while empty of water and in direct exposure to sunlight (this may cause solar heating distress). These are considered abuses and may invalidate this warranty.

*Operation of the **RECSPORT** Recreation System <u>does not</u> mean "use" of the **RECSPORT** Recreation System! Watkins Wellness does not recommend using the **RECSPORT** Recreation System if the water temperature is above or below the **RECSPORT** Recreation System's control panel temperature range.

DISCLAIMERS

Watkins Wellness shall not be liable for loss of use of the **ENDLESS POOLS RECSPORT** Recreation System, or other incidental, consequential, special, indirect, or punitive costs, expenses or damages, which may include but are not limited to the removal of a permanent deck or other custom fixture, or the necessity for crane removal. Any implied warranty shall have a duration equal to the duration of the applicable limited warranty stated above. Some states do not allow limitations on how long an implied warranty lasts. Under no circumstances shall Watkins Wellness or any of its representatives be held liable for injury to any person or damage to any property, however arising.

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you.

WATKINS WELLNESS CUSTOMER SERVICE

If you have any questions about any aspect of your **ENDLESS POOLS RECSPORT** Recreation System set-up, operation or maintenance that have not been answered by this manual, consult your **ENDLESS POOLS** dealer.

Watkins Wellness can be reached at: 800-999-4688 (extension 8432), Monday through Friday, 8 am to 5-pm Pacific Standard Time (PST), or e-mail customerservice@watkinsmfg.com.

TROUBLESHOOTING

Should you experience any problem whatsoever, do not hesitate to contact your authorized **ENDLESS POOLS** dealer. Located below and on the next page are some tips to help you to diagnose and rectify some more common sources of trouble yourself, if you choose to do so.

RECSPORT RECREATION SYSTEM WATER MAINTENANCE TROUBLESHOOTING GUIDE						
Problem	Probable causes	Solutions				
Cloudy Water	Dirty filters Excessive oils / organic matter Improper sanitization Suspended particles / organic matter Overused or old water	Clean filters Shock RECSPORT Recreation System with sanitizer Add sanitizer Adjust pH and/or alkalinity to recommended range Run jet pump(s) and clean filters Drain and refill the RECSPORT Recreation System				
Water Odor	Excessive organics in waterImproper sanitizationLow pH	Shock RECSPORT Recreation System with sanitizer Add sanitizer Adjust pH to recommended range				
Chlorine Odor	Chloramine level too high Low pH	Shock RECSPORT Recreation System with sanitizer Adjust pH to recommended range				
Musty Odor	Bacteria or algae growth	Shock RECSPORT Recreation System with sanitizer–if problem is visible or persistent, drain, clean and refill the RECSPORT Recreation System				
Organic buildup / scum ring around RECSPORT Recreation System	Build-up of oils and dirt	Wipe off scum with clean rag – if severe, drain the RECSPORT Recreation System, use a RECSPORT Recreation System surface and tile cleaner to remove the scum, and refill the RECSPORT Recreation System				
Algae Growth	High pH Low sanitizer level	Shock RECSPORT Recreation System with sanitizer and adjust pH Shock RECSPORT Recreation System with sanitizer and maintain sanitizer level				
Eye Irritation	Low pH Low sanitizer level	Adjust pH Shock RECSPORT Recreation System with sanitizer and maintain sanitizer level				
Skin Irritation / Rash	Unsanitary water Free chlorine level above 5 ppm	Shock RECSPORT Recreation System with sanitizer and maintain sanitizer level Allow free chlorine level to drop below 5 ppm before RECSPORT Recreation System use				
Stains	Total alkalinity and/or pH too low High iron or copper in source water	Adjust total alkalinity and/or pH Use a metal deposit inhibitor				
Scale	High calcium content in water – total alkalinity and pH too high	Adjust total alkalinity and pH – if scale requires removal, drain the RECSPORT Recreation System, scrub off the scale, refill the RECSPORT Recreation System and balance the water				

GENERAL OPERATION TROUBLESHOOTING GUIDE						
Problem	Probable causes	Solutions				
Entire RECSPORT Recreation System is inoperative	Power failure GFCI tripped Heater high-limit thermostat tripped	Check power source Reset GFCI; call for service if it will not reset Disconnect power for at least thirty seconds to reset heater high limit. If it will not reset, check for clogged filters. If tripping continues, call for service.				
RECSPORT Recreation System does not heat; jets and light operate	Integrated pressure switch open Circulation pump thermal cut-off tripped Water Care Mode	Check for clogged filters. Integrated pressure switch will reset when the flow of water through the heater has been restored. Call for service if the heater trips frequently. Check for clogged filters or air locks in plumbing. Disconnect power to the RECSPORT Recreation System, allow circulation pump to cool. Circulation pump thermal cut-off will reset when pump has cooled and power is reapplied. Call for service if circulation pump thermal cut-off trips frequently. Check which Water Care Mode your are in and change if necessary.				
Jets weak or surging	RECSPORT Recreation System water level too low Filters clogged Water valves are closed	Add water Clean filters Open water valves				
Lights inoperative	Light wiring or assembly is faulty	Call for service, replace light assembly				
RECSPORT Recreation System not heating properly	Temperature set too low RECSPORT Recreation System cover improperly positioned Dirty Filter Water Care Mode	Set control panel to a higher temperature. Align RECSPORT Recreation System cover Clean filter Check which Water Care Mode your are in and change if necessary.				
Pump motor will not function	Motor overload condition Control switch failure if jet symbol does not come on	Let cool for one hour. Motor overload will reset automatically. If problem persists, contact your ENDLESS POOLS dealer Disconnect RECSPORT Recreation System and contact your ENDLESS POOLS dealer				
Surging pump or motor	Low water level	Add water to normal level (6 inch (15 cm) below bar top)				
Pump motor runs, but low or no water/ jet pressure	 Air control valve closed Water Valves are closed Dirty filter cartridge Jet blocked Clogged suction or skimmer basket 	Open air valve Open any closed water valves Clean filter cartridge Remove jet face eyeball and clean orifice Clean suction cover or skimmer basket				
After filling or refilling the RECSPORT Recreation System: a jet pump is operating, but water is not flowing from any of its jets	Pump is not properly primed	Turn off power to the RECSPORT Recreation System at the breaker and remove the equipment compartment door. Loosen the union on the top of the pump(s) to allow the air to escape, and then hand-tighten the union(s). Turn power back on, activate the pump, and check to make sure the union is tight enough to keep it from leaking. Replace the equipment doors.				
"Heater Suspended" blinking	Turning temp down and up while heater is on.	System will automatically cycle and message will go off within 5 minutes.				

TROUBLESHOOTING ERROR CODES							
Error Code	Cause & Solution						
HR	An internal hardware error has been detected. Reset the breaker, if the problem persists, call for service.						
HL	The system has shut the heater down because the temperature at the heater has reached 119°F (48°C). Do not enter the water! Remove the cover and allow the water to cool down, then shut power off and power back up again to reset the system.						
АОН	Temperature inside the equipment compartment is too high, causing the internal temperature in the control box to increase above normal limits. Shut off power, open equipment compartment and allow area to cool. Close equipment compartment and repower once compartment has cooled down.						
FLO	The system does not detect any water flow while the primary pump is running. Check and open water valves. Check for water level. Clean filter. If the problem persists, call for service.						
Prr	A problem is detected with the temperature probe. Call for service.						
ОН	The water temperature has reached 108°F (42°C). Do not enter the water! Remove the cover and allow the water to cool down to a lower temperature. Call for service if problem persists.						
UPL	No low-level configuration software has been installed into the system. Call for service.						

RECSPORT RECREATION SYSTEM SPECIFICATIONS

This manual contains installation, operating, maintenance, and service information for the following **ENDLESS POOLS RECSPORT** Recreation System

THE SE STATE OF THE SE STATE O									
R200	12'0" x 7'5" 366 cm x 226 cm	50" 127 cm	100 ft²	4,000	1,335 gallons 5,054 liters	1,845 lbs 837 kg	14,730 lbs 6,680 kg	190 lbs/ft² 928 kg/ m²	230 volt, 30 amp Single phase GFCI protected circuit
R500	15'0" x 7'5" 457 cm x 226 cm	50" 127 cm	100 ft²	4,000	1,785 gallons 6,757 liters	2,055 lbs 932 kg	18,690 lbs 8,477 kg	195 lbs/ft² 952 kg/ m²	230 volt, 30 amp Single phase GFCI protected circuit

CAUTION: Watkins Wellness suggests a structural engineer or contractor be consulted before the **RECSPORT** Recreation System is placed on an elevated deck.

* NOTE: The "Filled weight" and "Dead weight" of the **RECSPORT** Recreation System includes the weight of 10 occupants (assuming an average occupant weight of 175 lbs (80 kg)).

©2020 WATKINS WELLNESS. ENDLESS POOLS IS A TRADEMARK OF WATKINS WELLNESS



Vista, California USA

