## LIMELIGHT® COLLECTION



FreshWater® Salt System Ready



Dual Action Filtration SilentFlo Circulation



FiberCor® High-Density Insulation



Color LCD Display

# FLASH



PeopleSeatingJetsVoltage7 SeatsOpen41 Jets230 V

#### Size

7' x 7' x 36" | 213 cm x 213 cm x 91 cm

#### **Water Care**

FreshWater® Salt System Ready



### LIMELIGHT® COLLECTION

# **FLASH**





#### **SHELL COLORS\***











Alpine Gray

Desert

Sun

#### **CABINET COLORS\***









Coastal Gray

Sable

Espresso

#### **COVER COLORS**







Slate

Caramel Chestnut

#### LEGENDARY MASSAGE

#### 41 Personalized-Control Jets

- 1 XL Dual Rotary jet
- 3 XL Single Rotary jets
- 1 XL Directional jet
- 4 Standard Single Rotary jets
- 4 Standard Directional jets
- 28 Directional Precision® jets

#### **EASY WATER CARE**

Water Care System FreshWater® Salt System Ready Filtration System Dual action, 100 sq. ft., top loading

#### LEADING ENERGY EFFICIENCY

Jet Pump 1 Wavemaster® 8200; Two-speed, 2.0 HP Continuous Duty,

4.0 HP Breakdown Torque

Jet Pump 2 Wavemaster® 8000; One-speed, 2.0 HP Continuous Duty,

4.0 HP Breakdown Torque

SilentFlo 5000® for quiet, continuous filtration **Circulation Pump** 

Titanium No-Fault® 4,000 W / 230 V Heater

Insulation FiberCor® Insulation; Certified to California

> Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas

Cover 3.5" to 2.5" tapered, 2 lb. density foam core

#### SIZE

**Dimensions** 7' x 7' x 36" / 213 cm x 213 cm x 91 cm

#### **CAPACITY**

**Seating Capacity** 7 seats

**Water Capacity** 360 gallons / 1,365 liters

Weight 845 lbs. / 385 kg dry; 5,070 lbs. / 2,300 kg filled\*\*

#### **ADDITIONAL FEATURES**

**Smart Spa** 

Hot Spring Spas App, Powered by the Connected Spa Kit

Technology

**Water Feature** Vidro® backlit ribbon waterfall

**Cover Lifters** CoverCradle®, CoverCradle II, Lift 'n Glide®, or UpRite®

Steps

Entertainment

Limelight Collection Step (Coastal Gray, Espresso, and Sable), Polymer Step (Ash) Bluetooth® Wireless Sound System (Optional)

**Control System** IQ 2020® with LCD control panel

230 V / 50 amp, 60 Hz

(Includes G.F.C.I. protected sub-panel)

Raio® multi-color interior points of light **Lighting System** 

Exterior multi-color lighting with timer

CoolZone™ (Optional) **Cooling System**